

Performance

Tipping load (ISO 14397-1)	2773 kg
Rated operating capacity (ISO 14397-1)	971 kg
Pump capacity	64.70 L/min
Pump capacity (with high flow option)	101.10 L/min
System relief at quick couplers	23.8-24.5 MPa
Max. travel speed (high range – optional)	16.0 km/h

Engine

Make / Model	Bobcat 2.4L, 97/68 EC
Compliance	Stage V
Fuel	Diesel
Cooling	Liquid
Power at 2600 RPM (ISO 14396)	50.8 kW
Torque at 1800 RPM (ISO 14396)	252.3 Nm
Number of cylinders	4
Displacement	2392 cm ³
Fuel tank	138.20 L

Weights

Operating weight	3664 kg
Shipping weight	3283 kg
Ground pressure	40.00 kPa

Controls

Vehicle steering	Hand Levers or optional Selectable Joystick Controls (SJC)
Loader hydraulics tilt and lift	Foot Pedals or optional Selectable Joystick Controls (SJC)
Front auxiliary (standard)	Proportional switch on Hand Levers or optional Selectable Joystick Controls (SJC)

Drive System

Transmission	Infinitely variable tandem hydrostatic piston pumps, driving two fully reversing hydrostatic motors
--------------	-----------------------------------------------------------------------------------------------------

Standard Features

Bobcat Interlock Control System (BICS)	Spark Arrester
Parking brake	Bob-Tach™ frame
Deluxe operator cab* Includes interior cab foam, side, top and rear windows, Deluxe wire harness, dome light and electrical power port ¹	Cushioned lift and tilt cylinders
Noise reduction kit	Lift arm support
Operating lights, front and rear	Engine/hydraulics system shutdown
Deluxe instrument panel	Automatically activated glow plugs
Keyless start with password capability	Electrically activated proportional front auxiliary hydraulics
Suspension seat	Auxiliary hydraulics: variable flow/maximum flow
Seat belt	Machine IQ (telematic)
Seat bar	Manual
Hydraulic bucket positioning (including ON/OFF switch)	CE certification
Tracks — rubber — 320 mm	Warranty: 24 months or 2000 hours (whichever occurs first)


1. Roll Over Protective Structure (ROPS) – meets requirements of SAE-J1040 and ISO 3471; Falling Object Protective Structure (FOPS) - meets requirements of SAE-J1043 and ISO 3449, Level I

Options

Deluxe pressurized cab with heating	Back-up alarm
Deluxe pressurized cab with HVAC	Radio
Selectable Joystick Controls (SJC - R/C Ready)	Beacon
Tracks - rubber - 400 mm	Work Lights LED
Cloth Suspension Seat	Road Option
High-flow auxiliary hydraulics	Automatic Ride Control
7-pin attachment control	Automatic Reversing Fan
2 Speed	Custom paint color (min order of 5 units)
Power Bob-Tach™	

Environmental

Operator LpA (98/37 & 474-1)	82 dB(A)
Noise level LWA (EU Directive 2000/14/EC)	101 dB(A)
Whole body vibration (ISO 2631-1)	0.84 ms ⁻²
Hand-arm vibration (ISO 5349-1)	2.29 ms ⁻²

Dimensions


(A)	3901.0 mm	(J)	3023.0 mm
(B)	1972.0 mm	(K)	887.0 mm
(C)	27.8°	(L)	42.0°
(D)	188.0 mm	(M)	97.0°
(E)	1402.0 mm	(N)	1727.0 mm
(F)	2657.0 mm	(N*)	1880.0 mm
(G)	3378.0 mm	(O)	2032.0 mm
(H)	30.0°	(Q)	1702.0 mm
(I)	2319.0 mm	(Q*)	1782.0 mm

Attachments

Auger Accessories	Planer Accessories
Augers	Planers
Backhoes	Rear Stabilizers
Bale Forks	Remote Control
Box Blades	Root Grapples
Breaker Accessories	Rotary Grinders
Breakers	Sand Cleaners
Brushcat™ Rotary Cutters	Scarifiers
Brush Saws	Scrapers
Combination Buckets	Seeders
Concrete Mixers	Skeleton Buckets
Concrete Pumps	Snow Blades
Construction / Industrial Buckets	Snow Pushers
Diggers	Snow V-Blades
Dozer Blades	Sod Layers
Drop Hammers	Soil Conditioners
Dumping Hoppers	Spreader
Flail Cutters	Spreaders
Forestry Cutters	Stump Grinders
Graders	Sweepers
Grapples, Industrial	Tillers
Landplanes	Tilt-Tatch
Landscape Rakes	Tree Transplanters
Laser Equipment	Trench Compactors
Low Profile Buckets	Trenchers
Miscellaneous	Utility Forks
Mixing Buckets	Utility Frames
Mowers	Vibratory Rollers
Pallet Fork Accessories	Wheel Saws
Pallet Forks, Hydraulic	Wood Chippers