

T250 Compact Track Loader

[Shop Parts, Fluids & More](#)

[Service Schedules](#)

[Order Manuals](#)

[Operator Training](#)

[Used Inventory](#)

T250 Specifications

	T250 (2005)	T250 Compact Track Loader	T250 Compact Track Loader (2008)
T250 Key Specifications			
Rated Operating Capacity (ISO)	2,500 lb	2,500 lb	2,500 lb
Operating Weight	9121 lb	9347 lb	9347 lb
Ground Pressure (Rubber)		3.8 psi	
Auxiliary High Flow	31.7 gal/min	37 gal/min	37 gal/min
Auxiliary Std Flow		21.2 gal/min	21.2 gal/min
Joystick Control	Not Applicable	Optional	Optional
Engine			
Engine Cooling	Liquid	Liquid	Liquid
Engine Fuel	Diesel	Diesel	Diesel
Horsepower	81 hp	81 hp	81 hp
Turbocharged Engine	yes	yes	yes
Emissions Tier (EPA)		Tier 3	Tier 2
Performance			
Rated Operating			

Rated Operating Capacity (ISO)	2,500 lb	2,500 lb	2,500 lb
Tipping Load	7143 lb	7358 lb	7358 lb
Operating Weight	9121 lb	9347 lb	9347 lb
Travel Speed	6.6 mph	6.6 mph	6.6 mph
Operating Capacity (50% of Tip)		3679 lb	3679 lb
Ground Pressure (Rubber)		3.8 psi	

Capacities

Fuel Tank	30 gal	26 gal	30 gal
-----------	--------	--------	--------

Hydraulic System

System Relief @ Quick Couplers	3,300 psi	3,300 psi	3,300 psi
Auxiliary High Flow	31.7 gal/min	37 gal/min	37 gal/min
Auxiliary Std Flow		21.2 gal/min	21.2 gal/min

Dimension

Length	114.9 in	114.9 in	114.9 in
Length without Attachment	114.9 in	114.9 in	114.9 in
Length with Standard Bucket	142.9 in	142.9 in	142.9 in
Width	78 in	78 in	78 in
Width (with bucket)	80 in	80 in	80 in
Height	80.9 in	80.9 in	80.9 in
Height with Operator Cab	80.9 in	80.9 in	80.9 in
Height to Bucket Hinge Pin	122.4 in	122 in	122.4 in
Reach @ Maximum Height	23.9 in	23.8 in	23.8 in
Turning Radius	82.4 in	82.4 in	82.4 in
Length of track on ground	63.7 in	63.7 in	63.7 in
Track Width	18 in	17.7 in	18 in
Track Width -		12 6 in	12 6 in

Optional

Features			
Joystick Control	Not Applicable	Optional	Optional
Air Conditioning	Optional	Optional	Optional
BICS System (Interlock)	Standard	Standard	Standard
Cab Heater	Optional	Optional	Optional
Operating Lights	Standard	Standard	Standard
Suspension Seat	Standard	Standard	Standard
Two Speed Travel	Not Applicable	Not Applicable	Not Applicable
Deluxe Instrumentation	Optional	Optional	Optional
Hydraulic Bucket Positioning	Optional	Optional	Optional
Auxiliary Hydraulics	Standard	Standard	Standard
Bob-Tach Attachment System	Standard	Standard	Standard
Backup Alarm		Standard	
Engine Shutdown		Standard	Standard
High Flow Option		Optional	Optional
Power Bob-Tach		Optional	Optional
ACS (Switchable Controls)		Optional	
Ride Control		Optional	Optional
Horn		Standard	
Power Qtach		Optional	Optional

Search for Parts

Search ↗



WARNING: *This product can expose you to chemicals including engine exhaust (including diesel engine exhaust when equipped), lead and lead compounds, mineral oils, soots, phthalates, and carbon monoxide which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.*

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.